

ZT3000



Bobcat®

One Tough Animal.

**BUILT FOR THE
TOUGHEST
CUSTOMER:
ME**

BRING TOUGH TO TURF

DELIVERS A QUALITY CUT

You're doing this because you love it. Pride in a job well done. That's the ZT3000's sweet spot, no matter how many acres you maintain.



ZT3000

MODEL NUMBER	9993001	9993002	9993003
ENGINE			
Model	Kaw FT651V	Kaw FT691V	Kaw FT730V
Maximum Power (SAE J1955)	20.5 hp	22.0 hp	23.5 hp
Displacement		44.3 cu.ci. (726 cc)	
Fuel Capacity		3.8 gal. (14.3 L)	
Air Filter		Dual Element	
ELECTRICAL			
Charging System		15 amp	
Clutch		125 lbf. (556 N)	
DECK			
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts		
Width	48.0 in. (1219 mm)	52.0 in. (1320 mm)	61.0 in. (1549 mm)
Adjustable Anti-Scalp Rollers	3	3	7
Cutting Height		1.5-4.8 in. (38-121 mm)	
Blade Tip Speed	17,365 fpm @ 3550 Engine rpm	18,142 fpm @ 3550 Engine rpm	18,809 fpm @ 3550 Engine rpm
Discharge Chute		Flexible Molded Polymer	
FRAME			
Front & Rear	Welded 7-gauge Steel; 1.5- x 2.5-inch Steel Tubing		
Machine Length		76.0 in. (1930 mm)	
Machine Weight	736 wet lb. (334 kg)	752 wet lb. (341 kg)	795 wet lb. (361 kg)
TRANSMISSION			
Type	HG ZT-3100 Hydrostatic Transaxles		
Pump Displacement		0.6 cu. in. (10 cc)	
Oil Capacity		4.0 qt. (3.8 L)	
Forward Speed		0-8.0 mph (0-12.8 km/hr.)	
Reverse Speed (mph)		0-3.5 mph (0-5.6 km/hr.)	
WHEELS			
Drive Wheel Size		22 x 11.0-10	
Front Caster Wheel Size		13 x 6.5-6	
Caster Arm Attachment		Welded to Frame	
SEAT			
Description	High-Back, EVC and Spring Suspension Seat		
Fore-Aft Adjustment	Seat Slide Lever		



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI. The gas engines in Bobcat mower are rated by the engine manufacturer under SAE J1955 using a certified horsepower testing procedure.



Bobcat is a Doosan company.

Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.
©2021 Bobcat Company. All rights reserved.



Bobcat®

Doosan Bobcat Korea Co., Ltd.
www.bobcat.com