

**ZT7000**



**Bobcat®**

*One Tough Animal.*

# MEAN BUSINESS

**BRING TOUGH TO TURF**

# BOOST YOUR BOTTOM LINE

The ZT7000 is the peak of toughness and best-in-the-business performance. With transport speeds up to 19 mph (30.5 km/h) and mowing speeds up to 13 mph (20.9 km/h), you can knock out quality results, job after job.



## ZT7000

MODEL NUMBER	9997010AU	9997011AU
<b>ENGINE</b>		
Model	Kaw FX1000V	
Maximum Power (SAE J1955)	35.0 hp	
Displacement	60.9 cu. in. (999 cc)	
Fuel Capacity	15.0 gal. (56.7 L)	
Air Filter	Canister Air Filter	
<b>ELECTRICAL</b>		
Charging System	15 amp	
Clutch	250 lbf. (1112 N)	
<b>DECK</b>		
Mower Deck	AirFX™ Cutting System	
Leading Edge	Adjustable, Front Lip Standard	
Width	61.0 in. (1549 mm)	72.0 (1828 mm)
Adjustable Anti-Scalp Rollers	6	7
Cutting Height	1.0-5.5 in. (25-139 mm)	
Blade Tip Speed	18,850 fpm @ 3550 Engine rpm	18,153 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	
<b>FRAME</b>		
Front & Rear	Welded, 0.25 in., 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing	
Machine Length	87.0 in. (2209 mm)	
Machine Weight	1500 wet lb. (680 kg)	1541 wet lb. (699 kg)
<b>TRANSMISSION</b>		
Type	HG ZT-5400 2-Speed Hydrostatic Transaxles	
Pump Displacement	0.9 cu. in. (16 cc)	
Oil Capacity	5.9 qt. (5.6 L)	
Forward Speed	0-19.0 mph (0-30.5 km/hr.)*	
Reverse Speed (mph)	0-7.5 mph (0-12.0 km/hr.)**	
<b>WHEELS</b>		
Drive Wheel Size	26 x 12.0-12	
Front Caster Wheel Size	15 x 6.5-6, No-Flat	
Caster Arm Attachment	Bolt-On	
<b>SEAT</b>		
Description	Extra-High Back, Full Mechanical Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	

\* 0-13 mph (0-20.9 km/h) cutting; 13-19 mph (20.9-30.5 km/h) transport

\*\* 5-7.5 mph (8.0-12.0 km/h) transport



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI. The gas engines in Bobcat mower are rated by the engine manufacturer under SAE J1955 using a certified horsepower testing procedure.



**Bobcat is a Doosan company.**

Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.  
©2021 Bobcat Company. All rights reserved.



# Bobcat®

Doosan Bobcat Korea Co., Ltd.  
www.bobcat.com